



## SCANIA 5 PIN PLUG TO 2 PIN PLUG CONVERSION



Earlier model Scania R-Series Trucks were all fitted with an electronically controlled Viscous Fan Drive (2 Pin Plug).

Later model Scania R Series Trucks are all fitted with an electronically controlled Viscous Fan Drive (5 Pin Plug).

The only part supplied as of April 2009 is the 5 Pin Plug.

If your vehicle is fitted with the earlier 2 Pin Plug please follow these steps:

1. Remove the **Orange wedge** from the 5 Pin Plug
2. Unclip each pin, then remove each wire complete with pin from the plug
3. Re-use the 2 Pin Plug from the old unit, insert the **Red** and **Blue** wires only from the new part into the old plug
4. Secure the remaining 3 wires individually and then to the main cable with electrical insulation tape

### NOTES

#### **2 Pin Plug**

Red Wire - 24v Solenoid Coil Positive

White/Blue Wire - 24v Solenoid Coil Ground

#### **5 Pin Plug**

Green Wire - Low Voltage Fan Speed Sensor Supply

Pink / Black Wire - Low Voltage Fan Speed Sensor Ground

Yellow Wire - Fan Speed Sensor Output

Blue Wire - 24V Solenoid Coil Ground

Red Wire - 24V Solenoid Coil Positive